

Test report : CEE-0309/25-1
CEE-0310/25-1
NB : 1722



Type: B
Fuel: Wood Logs



Vidago Eco 70; N° Série 03-02-00---

Red Pod – the soul of fire
www.red-pod.com mail@red-pod.com

N° DOP DD-053-B

Emissions (13%O₂):

	Nom	Part
CO :	1352 mg/m ³	-
NOx :	200 mg/m ³	-
OGC :	80 mg/m ³	-
PM :	40 mg/m ³	-

Performance:

	Nom	Part
P :	9,4 kW	-
P _w :	-	-
P _{SH} :	9,4 kW	-
η :	80 %	-
p :	12 Pa	-

EN 16510-1:2022 / EN 16510-2-2:2022

Flue gas outlet temperature (Nom-Part):	287 °C -
Diameter of the flue gas outlet :	180 mm
Fire safety of installation to the chimney :	T 400 G
Seasonal space heating efficiency (η _s) :	70 %
Energy Efficiency Index (EEI) :	106
Energy Efficiency Class :	A
The permissible maximum water operation pressure (P _w - bar):	-
Protective Insulation according to manufacturer's instructions :	40 mm
Power supply voltage (E) :	230 V
Power supply frequency (f) :	50 Hz
Maximum electric power input (W _{max}) :	30 W
Mass of the appliance (m) :	109 kg
Fuel Type :	Type I
Operation Type :	INT - Intermittent

Minimum distances to combustible materials

Bottom dB = 0 mm	Floor dF = 1500 mm
Ceiling dC = 1500 mm	Rear dR = 700 mm
Front dP = 1500 mm	Side dS = 300 mm
Non-Comb dnou = -	

Side radiation area dL = 1500 mm



Only use recommended fuels / Read and follow the manual / Shared flow prohibited